

Combi-Valve Quick Selection Guide

COMBI-VALVES							ACTUATORS					
Part No. SIEMENS	Part No. FRESE	DN	Min. Volumetric Flow l/h l/s		Max. Volumetric Flow l/h l/s		2-pos Thermic SR 230VAC	2-posThermic SR 24V AC/DC	0-10VDC Thermic SR 24VAC	0-10VDC NSR 24V AC/DC	3-pos NSR 24VAC	3-pos NSR 230VAC
VPI46 Series, Internal Thread	VPI46 Series, Internal Thread											
VPI46.15L0.2QS	VPI46.15L0.2QF-53-1362	15	30	0.01	200	0.06	STA23	STA73	STA63	SSA61EP	SSA81	SSA31
VPI46.15L0.6QS	VPI46.15L0.6QF-53-1364	15	100	0.03	575	0.16	STA23	STA73	STA63	SSA61EP	SSA81	SSA31
VPI46.20F1.4QS	VPI46.20F1.4QF-53-1368	20	220	0.06	1,330	0.37				SSA61EP	SSA81	SSA31
	VPI46.25F3.6QF-53-1373	25	600	0.17	3,609	1.00				SSA61EP	SSA81	SSA31
	VPI46.32F4QF-53-1374	32	550	0.15	4,001	1.11				SSA61EP	SSA81	SSA31

Part No. SIEMENS	Part No. FRESE	DN	Min. Volumetric Flow l/h l/s		Max. Volumetric Flow l/h l/s		3-pos NSR 24VAC	3-pos NSR 230VAC	0-10VDC NSR 24VAC
VPI45 Series, Internal Thread	VPI45 Series, Internal Thread								
VPI45.40F7QS	VPI45.40F7QF-53-1097	40	2,355	0.65	7,105	1.97	SQD85.03	SQD35.00	SQD65
VPI45.50F8.5QS	VPI45.50F8.5QF-53-1098	50	2,664	0.74	8,586	2.39	SQD85.03	SQD35.00	SQD65

Part No. SIEMENS	Part No. FRESE	DN	Min. Volumetric Flow l/h l/s		Max. Volumetric Flow l/h l/s		3-pos SR 24VAC	3-pos SR 230VAC	0-10VDC SR 24VAC	3-pos NSR 24VAC	3-pos NSR 230VAC	0-10VDC NSR 24VAC
VPF43 Series, Flanged (PN 16)	VPF43 Series, Flanged (PN 16)											
	VPF43.50F16F-53-1200	50	2,300	0.64	15,000	4.17	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.50F25F-53-1210	50	4,300	1.19	25,000	6.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.65F24F-53-1201	65	4,400	1.22	25,000	6.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.65F35F-53-1211	65	6,000	1.67	35,000	9.72	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.80F35F-53-1202	80	5,300	1.47	34,000	9.44	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.80F45F-53-1212	80	7,000	1.94	43,000	11.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF43.100F70F-53-1203	100	12,100	3.36	68,000	18.89	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF43.100F90F-53-1213	100	14,800	4.11	90,000	25.00	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF43.125F110F-53-1204	125	18,500	5.14	110,000	30.56	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF43.125F135F-53-1214	125	23,000	6.39	135,000	37.50	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF43.150F148F-53-1205	150	25,600	7.11	148,000	41.11	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF43.150F195F-53-1215	150	32,000	8.89	195,000	54.17	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00

Part No. SIEMENS	Part No. FRESE	DN	Min. Volumetric Flow l/h l/s		Max. Volumetric Flow l/h l/s		3-pos SR 24VAC	3-pos SR 230VAC	0-10VDC SR 24VAC	3-pos NSR 24VAC	3-pos NSR 230VAC	0-10VDC NSR 24VAC
VPF53 Series, Flanged (PN 25)	VPF53 Series, Flanged (PN 25)											
	VPF53.50F16F-53-1220	50	2,300	0.64	15,000	4.17	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.50F25F-53-1230	50	4,300	1.19	25,000	6.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.65F24F-53-1221	65	4,400	1.22	25,000	6.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.65F35F-53-1231	65	6,000	1.67	35,000	9.72	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.80F35F-53-1222	80	5,300	1.47	34,000	9.44	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.80F45F-53-1232	80	7,000	1.94	43,000	11.94	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAX81P03	SAX31P03	SAX61P03
	VPF53.100F70F-53-1223	100	12,100	3.36	68,000	18.89	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00
	VPF53.100F90F-53-1233	100	14,800	4.11	90,000	25.00	SQV91P40	SQV91P40 + ASP1.1	SQV91P40	SAV81P00	SAV31P00	SAV61P00